

# SAFETY DATA SHEET

## 1. PRODUCT AND COMPANY IDENTIFICATION

### Product Identifiers

Product Name: Artisan Acrylic Color Powder

### Recommended Use of the substance or mixture and Restrictions on Use

Industrial and professional cosmetic use

### Details of the Distributor of the Safety Data Sheet

#### **Distributor Address**

The Nail Superstore  
3804 Carnation St  
Franklin Park, IL 60131  
USA  
Website: www.nailsuperstore.com

### Emergency Telephone Numbers

**Company Phone Number:** 1(847)260-4000 (Mon-Fri 9:00 am - 5:30 pm CST)  
**Emergency 24-Hr. Telephone:** INFOTRAC: 1(800)535-5053 (Outside U.S: 1(352)323-3500)

## 2. HAZARDS IDENTIFICATION

### Classification of the substance or mixture

**Hazard Class - *Physical, Health, Environmental***

Eye Damage/Irritation

Skin sensitizer

**Category**

2A

1

### OSHA Defined Hazards

Combustible dust, may form combustible dust concentrations in air, explosion hazard

### Label Elements - Pictograms, Signal Word, Hazard Statements, Precautionary Statements, & Supplemental Information



### Signal Word

Warning

### Hazards Statements

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

### Precautionary Statements - Prevention, Response, & Disposal

P261 Avoid breathing dust/fume/gas/mist/vapours/spray

P264 Wash hands and exposed skin thoroughly after handling

P272 Contaminated work clothing should not be allowed out of the workplace

P280 Wear protective gloves/protective clothing/eye protection/face protection

P321 Specific treatment (see ... on this label)

P363 Wash contaminated clothing before reuse

P302+P352 IF ON SKIN: Wash with soap and water

|                    |   |
|--------------------|---|
| P305+P351<br>+P338 | IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing |
| P333+P313          | If skin irritation or a rash occurs: Get medical advice/attention   |
| P337+P313          | Get medical advice/attention  |
| P501               | Dispose of contents/container to an authorized disposal facility  |

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name   | Cas No.    | Weight-% | GHS Ratings   |
|---|------------|----------|---|
| 2-Propenoic acid, 2-methyl-, ethyl ester, polymer with methyl 2-methyl-2-propenoate | 25685-29-4 | 60 – 70  | Eye Damage/Irritation 2B (H320)                             |
| 2-Propenoic acid, 2-methyl-, ethyl ester, homopolymer                               | 9003-42-3  | 5 – 10   | Eye Damage/Irritation 2B (H320)                             |
| P(MMA/EA)   | 9010-88-2  | 1 – 5    | Eye Damage/Irritation 2B (H320)                             |
| Benzoyl Peroxide  | 94-36-0    | 1 – 5    | Eye Damage/Irritation 2A (H319)<br>Skin Sensitizer 1 (H317) |
| Aluminium Powder  | 7429-90-5  | 0 – 1    |   |

### 4. FIRST AID MEASURES

#### General Advice

Provide the SDS to medical personnel for treatment.

#### Inhalation:

Remove victim to fresh air. Seek immediate medical attention.

#### Eye Contact:

If product gets in the eyes, flush with lukewarm water for at least 15 minutes. If irritation occurs, contact a physician.

#### Skin Contact:

Rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately.

#### Clothing:

Remove contaminated clothing, wash thoroughly before reuse.

#### Ingestion:

If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give anything by mouth to an unconscious person. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. Get medical attention immediately.

### 5. FIRE-FIGHTING MEASURES

#### Suitable Extinguishing Media

---

Water, Chemical (alcohol-resistant) foam, dry chemical, or carbon dioxide.

#### **Unsuitable Extinguishing Media**

Water may not be effective in extinguishing this fire.

#### **Specific Hazards Arising from the Chemical**

Polymers are combustible dusts, care should be taken to avoid creating explosive concentrations in the air. Follow grounding and bonding procedures.

#### **Special Fire Fighting Procedures:**

Avoid extinguishing methods, which may generate dust clouds. Water stream can disperse dust into air producing a fire hazard and possible explosion hazard if exposed to ignition source. Firefighters should wear self-contained breathing apparatus.

#### **Protective Equipment and Precautions for Firefighters**

Polymer dust is combustible. The explosive limits of the polymer particles suspended in air are approximately those of coal dust. Polymers are sensitive to static discharge, follow grounding and bonding procedures. Polymers are not sensitive to mechanical impacts.

## **6. ACCIDENTAL RELEASE MEASURES**

#### **Personal Precautions, Protective Equipment and Emergency Procedures**

##### **Personal Precautions**

Before cleaning any spill or leak, individuals must wear appropriate Personal Protective Equipment that is specified in section 8. Keep airborne particulates at a minimum when cleaning up spills. Deny entry to all unprotected individuals. Remove any contaminated clothing and wash thoroughly before reuse.

##### **Environmental Precautions**

Extinguish all ignition sources. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

#### **Methods and Material for Containment and Cleaning Up**

##### **Methods for Containment**

Prevent further leakage or spillage if safe to do so. Dike and contain spill with inert material (e.g. sand or earth). May contaminate water supply.

##### **Methods for Cleaning Up**

Maximize ventilation (open doors and windows) and secure all sources of ignition. Use good, local ventilation with a minimum capture velocity of 100 ft/min (30 m/min) at point of product release. Place into appropriate closed container(s) for disposal in accordance with local, state and federal regulations. Wash all affected areas with plenty of warm water and soap. Not a RCRA Hazardous waste.

## **7. HANDLING AND STORAGE**

#### **Precautions for Safe Handling**

##### **Advice on Safe Handling**

Use in well ventilated areas. Avoid contact with skin, eyes and clothing. Avoid breathing dust. Use good personal hygiene and housekeeping. Avoid prolonged contact with the product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.

#### **Conditions for Safe Storage, Including any Incompatibilities**

### Storage Conditions

Store containers in a cool, dry location, away from direct sunlight, heat, sparks, flame, other light sources, or sources of intense heat. The temperature should remain at or under 72°F (22°C) at all times. Storing above recommended temperature will cause product performance issues. Store in accordance with National Fire Protection Association recommendations. Observe all label precautions until the container is cleaned, reconditioned, or destroyed.

### Incompatible Materials

Strong oxidizers, strong oxidizing agents.

| 8. EXPOSURE CONTROLS/PERSONAL PROTECTION  |  |                                   |   |
|---|--|-----------------------------------|---|
| Chemical Name / CAS No.   | OSHA Exposure Limits   | ACGIH Exposure Limits             | Other Exposure Limits   |
| 2-Propenoic acid, 2-methyl-, ethyl ester, polymer with methyl 2-methyl-2-propenoate<br>25685-29-4 |  |                                   |   |
| 2-Propenoic acid, 2-methyl-, ethyl ester, homopolymer<br>9003-42-3                                |  |                                   |   |
| P(MMA/EA)<br>9010-88-2  |  |                                   |   |
| Benzoyl Peroxide<br>94-36-0   | 5 mg/m3 TWA  | 5 mg/m3 TWA                       | NIOSH: 5 mg/m3 TWA  |
| Aluminium Powder<br>7429-90-5   | 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction) | 1 mg/m3 TWA (respirable fraction) | NIOSH: 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust) |

### Engineering Controls

Use local explosion-proof ventilation that is adequate to keep employee exposure to airborne concentrations below exposure limits. Please refer to the ACGIH document, Industrial Ventilation, A Manual of Recommended Practices, most recent edition, for details.

### Personnel Protective Equipment (PPE)

#### Respiratory Protection

A respirator should be worn whenever workplace conditions warrant use of a respirator. If dust conditions are present, a N95 respirator dust mask is required. None required if airborne concentrations are maintained below any exposure limit that may be listed above. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134 or other appropriate governing standard.

#### Eye/Face Protection

Wear safety glasses, chemical goggles when splashing is possible, when dealing with this material. If necessary, refer to U.S. OSHA 29 CFR §1910.133, or other appropriate governing standard. Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.

#### Skin and Body Protection

Complete suit protecting against chemicals, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact:

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm

Break through time: 480 min

Splash contact:

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 120 min

### General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling. An eyewash station and a safety shower are recommended. Food, beverages, and tobacco products should not be carried, stored, or consumed where this material is in use. Wash hands thoroughly before eating, drinking, or smoking.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|   |  |
|---|--|
| <b>Appearance:</b> Red-Gold<br><b>Odor:</b> Faint<br><b>Flammable Limit (Air Volume%, N/A Lower/Upper)</b><br><b>Evaporation Rate</b> No data available<br><b>Specific Gravity</b> 1.47 | <b>Physical State:</b> Powder<br><b>Flash Point:</b> 577°F,303°C<br><b>Autoignition Temperature:</b> 80°C<br><b>Boiling Range (low - high)</b> N/A |
|---|--|

## 10. STABILITY AND REACTIVITY

### Material stability

Stable

### Incompatible materials

Strong oxidizers

### Hazardous decomposition products

Methacrylate Monomer and Oxides of Carbon when burned

### Possibility of hazardous reactions

Hazardous polymerization will not occur.

## 11. TOXICOLOGICAL INFORMATION

### Mixture Toxicity

### Component Toxicity

### Routes of Exposure

Inhalation      Eye Contact

### Target Organs

Eyes      Skin      Respiratory System

### Effects of Overexposure

### Product Components Listed as Carcinogenic

| <u>CAS Number</u> | <u>Description</u> | <u>% Weight</u> | <u>Carcinogen Rating</u> |
|-------------------|--------------------|-----------------|--------------------------|
| 7429-90-5         | Aluminium Powder   | 0.1 to 1.0%     | Aluminium Powder:        |

## 12. ECOLOGICAL INFORMATION

**Component Ecotoxicity**

**13. DISPOSAL CONSIDERATIONS**

**Waste Treatment Methods**

**Disposal of Wastes**

Dispose waste material in accordance with Federal, State, and Local regulations. It is the responsibility of the generator to determine at the time of disposal whether the product meets the criteria of a hazardous waste. Comply with all applicable federal, state and local regulations. Waste disposal options include landfilling solids at permitted sites. Incinerate in a chemical incinerator equipped with an afterburner and scrubber. Use registered transporters.

**Contaminated Packaging**

Reuse of empty drums or containers is not recommended. Employees should be advised of the potential hazards, due to residual flammable material, associated with empty containers. Dispose of all empty containers properly, in accordance with Federal, State and Local regulations

**14. TRANSPORT INFORMATION**

| <u>Agency</u> | <u>Proper Shipping Name</u> | <u>UN Number</u> | <u>Packing Group</u> | <u>Hazard Class</u> |
|---------------|-----------------------------|------------------|----------------------|---------------------|
| DOT           | Not Regulated, Polymer, NOS |                  |                      |                     |
| IATA          | Not Regulated, Polymer, NOS |                  |                      |                     |
| IMDG          | Not Regulated, Polymer, NOS |                  |                      |                     |

**15. REGULATORY INFORMATION**

**State of California Safe Drinking Water and Toxic Enforcement Act of 1986**

**(Proposition 65):** WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- None

**SARA 313**

Aluminium Powder 7429-90-5  
Benzoyl Peroxide 94-36-0

**US State Right-to-Know Regulations**

- None

| <u>Country</u> | <u>Regulation</u>      | <u>All Components Listed</u> |
|----------------|------------------------|------------------------------|
|                | EINECS                 | Yes                          |
|                | SARA Hazard categories | No                           |
|                | TSCA Inventory         | Yes                          |


**16. OTHER INFORMATION**

**Hazardous Material Information System (HMIS)**

|                            |                                |
|----------------------------|--------------------------------|
| <b>HEALTH</b>              | <input type="text" value="1"/> |
| <b>FLAMMABILITY</b>        | <input type="text" value="1"/> |
| <b>PHYSICAL HAZARD</b>     | <input type="text" value="0"/> |
| <b>PERSONAL PROTECTION</b> | <input type="text" value="B"/> |

**HMIS & NFPA Hazard Rating Legend**  
 \* = Chronic Health Hazard  
 0 = INSIGNIFICANT  
 1 = SLIGHT  
 2 = MODERATE  
 3 = HIGH

**National Fire Protection Association (NFPA)**



Date Prepared: 07/14/16  
2016-07-14

Reviewer Revision 1

---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not considered a warranty or quality specification. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials on in any process, unless specified in the text.