

Material Safety Data Sheet Artisan uControl Ultra White Builder Gel Page 1 of 6

Section 1 – Identification

Product Name: Artisan uControl Ultra White Builder Gel

Distributor: The Nail Superstore

3804 Carnation St., Franklin Park, IL 60131

Chemical Name: N/A

Information Contacts: (847) 260-4000

Emergency Phone Numbers: US & Canada: (800) 535 - 5053

Family: UV GELS

GEL Type: TYPE 5

Product Use: NAIL GEL

Emergency Phone Number: International: 1-352-323-3500

Section 2 – Hazards Identification

EMERGENCY OVERVIEW

This information is based on findings from related or similar materials.

- May be slightly toxic.
- May cause moderate skin injury (reddening & swelling).
- May cause chemical burn in eye.

Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry No specific information available.

Eye No specific information available. Contains materials that are essentially nonirritating, but contact may cause slight transient irritation.

Skin No specific information available. Contains materials that may cause moderate skin injury (reddening and swelling) and/or sensitization. Prolonged contact may cause blister formation (burns). Since irritation may not occur immediately, contact can go unnoticed.

Ingestion No specific information available. Contains materials that may be practically nontoxic.

Inhalation No specific information available. Low volatility makes vapor inhalation unlikely. Aerosol can be irritating.

Sub-Chronic Effects No specific information available. Limited tests showed no evidence of teratogenicity in animals. A lifetime skin painting study with mice showed no evidence of carcinogenicity.

NOTE: Refer to Section 11, Toxicological Information for Details

Section 3 – Composition/Information on Ingredients

Chemical Identity	CAS#	EINECS#	INCI (or other substance) Name	Exposure OSHA TWA/STEL	Limits ACGIH TWA/STEL	Carcinogen IARC/NTP/OSHA	%
Polyurethane Acrylate Oligomer	Exempt	N/E	Di-Hema Trimethylhexyl Dicarbamate*	N/E	N/E	Not Listed	75-80
Tripropylene Glycol Diacrylate Esters (TPGDA)	42978-66-5	256-032-2	N/E	N/E	N/E	Not Listed	10-15
Ethoxylated Trimethylolpropane triacrylate esters (ETPTA)	28961-43-5	N/DA	N/E	N/E	N/E	Not Listed	3-5
Silicon Dioxide	60676-86-0	262-373-8	Silica	N/E	N/E	Not Listed	3-5
Hydroxycyclohexyl phenyl ketone	947-19-3	213-426-9	Hydroxycyclohexyl phenyl ketone	N/E	N/E	Not Listed	0-1
Benzophenone	119-61-9	204-337-6	Benzophenone	N/E	N/E	Not Listed	0-1
Titanium Dioxide	13463-67-7	236-675-5	CI77891	15 mg/m3	10 mg/m3	Group 3/No/No	0-1
D&C Violet #2	81-48-1	201-353-5	CI60725	N/E	N/E	Not Listed	0-1
N/E – None Established N/R – Not Reviewed	N/DA – No Data Available N/A – Not Applicable	* See section 16					

Polyurethane Acrylate Oligomer: Hazard Symbol: Xi Risk Phrases: R36/37/38 Safety Phrases: S14, S3/7, S62

Tripropylene Glycol Diacrylate Esters (TPGDA): Hazard Symbol – Xi, N Risk Phrases – R36/37/38, R43, R51/53 Safety Phrases – S2, S24, S37, S61

Ethoxylated Trimethylolpropane triacrylate esters (ETPTA): Hazard Symbol – Xi Risk Phrases – R36/37/38 Safety Phrases – S26, S36

Silicon Dioxide: Hazard Symbol – Xn Risk Phrases – R20, R48 Safety Phrases – S22, S38

See Section 16 for Risk and Safety Phrase Key

Material Safety Data Sheet Artisan uControl Ultra White Builder Gel

Section 4 – First Aid Measures

First Aid for Eye	Flush with plenty of water for 15 minutes and seek medical attention.
First Aid for Skin	Remove contaminated clothing and wash contact area with soap and water for 15 minutes.
First Aid for Inhalation	In case of exposure to a high concentration of vapor or mist, remove person to fresh air. If breathing has stopped, administer artificial respiration and seek medical attention.
First Aid for Ingestion	If appreciable quantities are swallowed, seek medical attention.

Section 5 – Fire Fighting Measures

Flash Point (°F/°C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)
> 212°F/100°C Setaflash	No Data	No Data

Method:

Extinguishing Media:	Use carbon dioxide or dry chemical for small fires; aqueous foam or water for large fires.
Fire Fighting Instructions:	Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering confined areas where potential for exposure to vapors or products of combustion exists.
Unusual Hazards:	High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the violent rupture of storage vessels or containers. Avoid the use of a stream of water to control fires since frothing can occur.

Section 6 – Accidental Release Measures

Spill or Release Procedures	Spontaneous polymerization can occur. Eliminate ignition sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Absorb with inert material and dispose of properly. Flush area with water; prevent washings from entering waterways.
-----------------------------	---

Section 7 – Handling and Storage

Handling	Avoid contact with skin and eyes. Avoid breathing vapor. Keep container closed when not in use. Avoid prolonged exposure to light. Remove all contaminated clothing, shoes, belts and other leather goods immediately. Incinerate leather goods (including shoes). Wash contaminated clothing thoroughly before reuse. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased penetration potential. When handling gel for product use, do not heat above 100°F/38°C or disassociation of silica in product may occur. Material is UV light sensitive, avoid prolonged exposure to light/heat.
Storage	Store in a cool place, away from heat and light. Store at temperatures below 100°F/38°C.
Explosion Hazard	High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the violent rupture of storage vessels or containers.

Section 8 – Exposure Controls / Personal Protection

Engineering Controls	Local exhaust recommended to control exposure which may result from operations generating aerosols and hot operations generating vapors.
----------------------	--

Personal Protective Equipment

General	To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC. A safety shower and eye wash facility should be readily available.
Eye/ Face Protection	Chemical splash goggles. Contact lenses should not be worn.
Skin Protection	Impervious gloves (Butyl rubber, Neoprene, and/or Nitrile).
Respiratory Protection	A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by nuisance level organic vapor dust masks can be used, however the use of the respirator is limited. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149.

Material Safety Data Sheet Artisan uControl Ultra White Builder Gel

Section 9 – Physical and Chemical Properties

Appearance	Odor & Odor Threshold	pH	Specific Gravity	Viscosity	% Volatile		
White, viscous liquid	characteristic acrylate odor	NA	(H2O=1) : 1.15	N/DA	By Volume : < 0.5		
Boiling Point/ Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure: mmHg	Vapor Density	Evaporation Rate	Ignition	Solubility In Water (20°C)
N/A	N/A	N/A	@ 20 C : < 0.01	No Data	No Data	No Data	Insoluble
Flash Point (°F/°C)		Flammable Limit (vol%)		Auto-ignition Temperature (vol%)			
> 212°F/100°C Setaflash		No Data		No Data			

Section 10 – Stability and Reactivity

Stability

Normally Stable

Hazardous Decomposition Products:

Fumes produced when heated to decomposition may include: carbon monoxide, carbon dioxide.

Conditions to Avoid:

Storage >100°F/38°C, exposure to light, loss of dissolved air, loss of polymerization inhibitor, contamination with incompatible materials.

Incompatibility (Materials to Avoid):

Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust and string bases.

Hazardous Polymerization:

May occur -- Uncontrolled polymerization may cause rapid evolution of Heat and increased pressure that could result in violent rupture of sealed storage vessels or containers.

Section 11 – Toxicological Information

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation – skin	Irritation – Eye
N/DA	N/DA	N/DA	N/DA	N/DA
Sensitization		Mutagenicity		Sub-chronic Toxicity
N/DA		N/DA		N/DA

Section 12 – Ecological Information

Ecotoxicological Information

Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
N/DA	N/DA	N/DA	N/DA	N/DA

Chemical Fate Information

Biodegradability	N/DA
Chemical Oxygen Demand	N/DA

Section 13 – Disposal Considerations

Non-contaminated, properly inhibited product is not a RCRA hazardous waste. It is the generators responsibility to determine what is classified as a hazardous waste. Comply with all federal, state, and local regulations.

Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate.

Section 14 – Transport Information

DOT (49 CFR 172)	
Proper Shipping Name:	Non-Regulated Material
Identification Number:	N/A
Marine Pollutant:	No
Special Provisions:	N/A
Emergency Response Guidebook (ERG) #:	N/A
IATA (DGR):	
Proper Shipping Name:	Non-Regulated Material
Class or Division:	N/A
UN or ID Number:	N/A
Packaging Instructions:	

Material Safety Data Sheet Artisan uControl Ultra White Builder Gel Page 4 of 6

Emergency Response Guidance (ICAO)#:	
IMO (IMDG):	
Proper Shipping Name:	Non-Regulated Material
Class or Division:	N/A
UN or ID Number:	N/A
Special Provisions & Stowage/Segregation:	None
Emergency Schedule (EmS)#:	
Other Information:	Flash point > 100°C

Section 15 – Regulatory Information**US Federal Regulations**

Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP and ODS's), as defined by the U.S. Clean Air Act: <ul style="list-style-type: none"> • Benzophenone (SOCMI Chemical). This product does not contain any Class 1 or Class 2 ODS.
Clean Water Act: Priority Pollutant	This product contains the following Hazardous Substances as defined by the CWA: <ul style="list-style-type: none"> • NONE This product does not contain any substances that are a Priority Pollutant or Toxic Pollutant under the CWA.
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and / or other applications as an indirect food additive.
Occupational Safety and Health Act	This product is considered to be a hazardous chemical under the OSHA Hazard Communication Standard. Its hazards are: <ul style="list-style-type: none"> • Immediate (acute) health hazard • Delayed (chronic) health hazard • Reactive hazard
RCRA	This product is not considered to be a hazardous waste under RCRA (40 CFR 261).
SARA Title III: Section 302 (TPQ)	This product contains no chemicals regulated under Sec. 302 as extremely hazardous substances that carry a TPQ.
SARA Title III: Section 302 (RQ)	This product contains no chemicals regulated under Section 304 as extremely hazardous chemical for emergency release notification (" CERCLA" List).
SARA Title III: Section 311-312:	This product is considered hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazards are: <ul style="list-style-type: none"> • Immediate (acute) health hazard • Delayed (chronic) health hazard • Reactive hazard
SARA Title III: Section 313:	This product contains no chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.
TSCA Section 8(b): Inventory:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements.
TSCA Significant New Use Rule:	None of the chemicals listed have a SNUR under TSCA.

State Regulations

CA Right-to-Know Law:	Silicone Dioxide CAS#60676-86-0.
California No Significant Risk Rule:	NONE
MA Right-to-Know Law:	Silicone Dioxide CAS#60676-86-0.
NJ Right-to-Know Law:	Silicone Dioxide CAS#60676-86-0.
PA Right-to-Know Law:	Silicone Dioxide CAS#60676-86-0.
FL Right-to-Know	Silicone Dioxide CAS#60676-86-0.
MN Right-to-Know	Benzophenone CAS #119-61-9, Silicone Dioxide CAS#60676-86-0.

International Regulations

CDSL: Canadian Inventory (on Canadian Transitional List)	Benzophenone CAS #11-61-9 is on the DSL list. WHMIS = n/da Hydroxycyclohexyl phenol ketone CAS # 947-19-3 is on the DSL list. WHMIS = n/da Tripropylene Glycol Diacrylate Esters (TPGDA) CAS #42978-66-5 is on the DSL list. WHMIS= n/da Ethoxylated Trimethylolpropane triacrylate esters (ETPTA) CAS# 28961-43-5 is on the DSL list. WHMIS= n/da Silicone Dioxide CAS#60676-86-0 is on the DSL list. WHMIS = n/da
--	---

Material Safety Data Sheet Artisan uControl Ultra White Builder Gel Page 5 of 6

Titanium Dioxide CAS #13463-67-7 is on the DSL list. WHMIS = n/da

Labeling according to EC directives – 1999/45/EC

European Community:



Prima Ultra White Builder Gel:

- HAZARD SYMBOLS: **Xi**: Irritant
- RISK PHRASES: **R22**: Harmful if swallowed, **R36/38**: Irritating to eyes and skin, **R43**: May cause sensitization by skin contact.
- SAFETY PHRASES: **S18**: Handle and open container with care, **S24/25**: avoid contact with skin and eyes, **S36/37**: Wear suitable protective clothing and gloves, **S38**: in case of insufficient ventilation, wear suitable respiratory equipment.

Section 16 – Other Information

EU Classes and Risk / Safety Phrases for Referenced Ingredients (See Section 2):

Hazard Symbol:

Xi – Irritants

Xn – Harmful preparations and substances

N – Substances or preparations which are dangerous to the environment

Risk Phrases:


R20 Harmful by inhalation; R36/37/38 Irritating to eyes, respiratory system and skin; R43 May cause sensitization by skin contact; R48 Danger of serious damage to health by prolonged exposure; R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Safety Phrases:


S2 Keep out of the reach of children; S3/7 Keep container tightly closed in a cool place; S22 Do not breathe dust; S24 Avoid contact with skin; S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice; S36 Wear suitable protective clothing; S37 Wear suitable gloves; S38 In case of insufficient ventilation wear suitable respiratory equipment; S61 Avoid release to the environment. Refer to special instructions/safety data sheet; S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label

Hazard Rating System (Pictograms)

NFPA:



HMIS:



* - Respiratory protection may be necessary depending on conditions of use. Refer to Section VIII of this MSDS for respiratory protection guidelines.

OSHA PEL for nuisance dust: 15 mg/m³ (total dust)
5 mg/m³ (respirable dust)

ACGIH PEL for nuisance dust: 10 mg/m³

MSDS Prepared:

1/25/10

Revision History:

11/24/04 Update section 2 contents and format updates throughout.

04/30/08 Updated INCI name for Polyurethane Acrylate Oligomer.

* Most Keystone gels are composed of oligomers made primarily from urethane methacrylates. Keystone is using the designation Di HEMA Trimethylhexyl Dicarbamate, the official INCI name of urethane dimethacrylate, which is substantially the equivalent of Polyurethane Acrylate Oligomer.

09/17/08 Updated section 16

10/22/08 Updated format

Material Safety Data Sheet **Artisan uControl Ultra White Builder Gel** Page 6 of 6

	12/10/08 Updated Risk and Safety Phrases
	03/18/09 Updated to meet Globally Harmonized System requirements. Added the EU address to section 1. Switched location of section 2 with section 3. Changed the title in sections 1, 8, and 13. Moved MSDS preparation to section 16.
	01/25/10 Added international emergency phone number to section 1

The data contained herein is based upon information that The Nail Superstore believes to be reliable. Users of this product have the responsibility to determine the suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and involved in said use. All statements or suggestions are made without warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material or results to be obtained from the use thereof.