Material Safety Data Sheet

Section 1. 0	Chemical Product and Company Identification	
Common Name	Artisan EZ Dipper Top	. Code #139024 #139025
D: . : 1		MSDS# 3-TB-20-0198
Distributor	3804 Carnation St, Franklin Park, IL 60131	Validation Date 12/3/2001
Synonym	· Not available.	Print Date 12/3/2001
Trade name	TB1785 Thick	Responsible Name Company
Material Uses	Industrial applications: Cyanoacrylate adhesive	In Case of Emergency (800) 535-5053

Section 2. Composition, Information on Ingredients			
Name	CAS#	% by Weight	Exposure Limits
1) Ethyl 2-cyanoacrylate	7085-85-0	90-95	TWA: 0.2 (ppm) from ACGIH (TLV) TWA: 1 (mg/m³) from ACGIH (TLV)

Liquid. (Transparent Liquid.)		
EMERGENCY OVERVIEW		
Combustible liquid. Rapid polymerization occurs upon contact with water or alkaline sustances. Skin inflamation or burns may occur upon contact during this polymerization. Will bond skin.		
May cause mucous membrane and respiratory tract damage. Use with adequate ventilation.		
Wear suitable protective clothing and gloves. Store and use away from heat, sparks, open flame, or any other ignition source (See section 8).		
Inhalation.		
Slightly hazardous in case of eye contact (irritant). Bonds skin instantly.		
Concentrated vapors are hazardous if inhaled.		
No known hazard		
Repeated use may result in irritation of mucous membrane and upper respiratory tract.		
Repeated or prolonged exposure is not known to aggravate any medical conditions.		

Page:	2/6
-------	-----

Eye Contact	IMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. Do not attempt to pull apart bonded eyelid. Seek medical attention.	
Skin Contact	After contact with skin, wash immediately with plenty of water. Gently and thoroughly wash the contaminated skin with running water and soap. Seek medical attention to remove cured material. Was contaminated clothing before reusing.	
Inhalation	If symptoms of prolonged exposure to concentrated material vapors appear, remove to fresh air. If breathing is difficult, loosen any restrictive clothing and provide oxygen and get medical care if necessary.	
Ingestion	Do not induce vomiting. Saliva will cause cyanoacrylate to polymerize in the mouth. If lips are bonded together, use warm water to gently separate the lips apart.	
Notes to Physician	Cured adhesive does not pose a health risk	

Section 5. Fire Fight	ing Measures
Flammability of the Product	Combustible.
Auto-Ignition Temperature	>200°C (392°F)
Flash Points	The lowest known value is CLOSED CUP: 79°C (174.2°F). (Ethyl 2-cyanoacrylate)
Flammable Limits	Not available.
Products of Combustion	Not available.
Fire Hazards in Presence of Various Substances	Not available.
Explosion Hazards in Presence of Various Substances	None known
Fire Fighting Media and Instructions	SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray, fog or foam. Do not use water jet.
Protective Clothing (Fire)	Vapor respirator or a self contained breathing apparatus.
Special Remarks on Fire Hazards	No additional remark.
Special Remarks on Explosion Hazards	No additional remark.

Section 6. Accidental Release Measures		
Small Spill and Leak	Absorb with an inert material and put the spilled material in an appropriate waste disposal.	
Large Spill and Leak	Combustible material. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.	

Section 7. Ha	indling and Storage
Handling	To avoid fire, minimize ignition sources. Avoid contact with skin and eyes. In case of insufficient ventilation, wear suitable respiratory equipment. May react in presence of moisture. May react or be incompatible with alkalies.
Storage	Contains moisture sensitive material; store in a dry place. Keep away from sources of ignition. Keep container tightly closed and dry. Keep in a cool, well-ventilated place.

Section 8. Exposure Controls, Personal Protection

Engineering Controls

Good general ventilation should be sufficient to control airborne levels in small quantity use. Local exhaus is recommended for bulk repackaging or continuous large quantity use.

Personal Protection

Eyes Safety glasses.

Body Synthetic apron.

Respiratory Wear appropriate respirator when ventilation is inadequate.

Hands Gloves (impervious).

Feet Wear chemical resistant shoes

Protective Clothing (Pictograms)



Personal Protection in Case of a Large Spill

A self contained breathing apparatus should be used to avoid inhalation of the product. Boots. Full suit. Gloves. Safety glasses.

Product Name

Exposure Limits

1) 2-Propenoic acid, 2-cyano-, ethyl ester

TWA: 0.2 (ppm) from ACGIH (TLV) TWA: 1 (mg/m³) from ACGIH (TLV)

Consult local authorities for acceptable exposure limits.

Physical State and Appearance	Liquid. (Transparent Liquid.)	Odor	Acrid.
Molecular Weight	Mixture.	Taste	Not available.
Molecular Formula	Mixture.	Color	Transparent.
pH (1% Soln/Water)	Not applicable.		
Boiling/Condensation Point	The lowest known value is >190°C (374°F) (Ethyl 2-cyanoacrylate).		
Melting/Freezing Point	Not available.		
Critical Temperature	Not available.		
Specific Gravity	1.05 (Water = 1)		
Vapor Pressure	0.0075 mm of Hg (@ 20°C)		
Vapor Density	The highest known value is >1 (Air = 1) (Ethyl 2-cyanoacrylate).		
Volatility	Not available.		

TB1785		Page: 4/6
Odor Threshold	Not available.	
Evaporation Rate	Not available.	
voc	Not available.	
Viscosity	Kinetic: 85 cP	
LogK _{ow}	Not available.	
Ionicity (in Water)	Not applicable.	
Dispersion Properties	Not available.	
Solubility	Insoluble in cold water.	v
Physical Chemical Comm	ents Insoluble in water	lada a Kira kira kira kira kira kira kira kira k

Section 10. Stability	and Reactivity	
Stability and Reactivity	The product is stable but it is water reactive.	
Conditions of Instability	Rapid polymerization occurs upon contact with water or alkaline sustances. As a result, heat is generated. Skin inflamation or burns may occur upon contact during this polymerization.	
Incompatibility with Various Substances	Reactive with alkalis, moisture, peroxides.	
Hazardous Decomposition Products	Not available.	
Hazardous Polymerization	Yes due to heat generated during polymerization.	

Section 11. Toxicological Information			
Toxicity to Animals	LD50: Not available. LC50: Not available.		
Chronic Effects on Humans	The substance is toxic to mucous membranes, upper respiratory tract.		
Other Toxic Effects on Humans	Slightly hazardous in case of skin contact (irritant). Concentrated vapors are hazardous in inhaled.		
Special Remarks on Toxicity to Animals	Not available.		
Special Remarks on Chronic Effects on Humans	Continous high volume usage without adequate ventillation can irritate eyes and nose.		
Special Remarks on Other Toxic Effects on Humans	Vapors are irritating to mucous membrane and upper respirator tract. Under normal conditions of use of this product, no respiratory protection is required. Aproved breathing apparatus is required if large spill occurs.		

Ecotoxicity	Not available.
BOD5 and COD	Not available.
Biodegradable/OECD	Not available.
Mobility Products of Degradation	Not available.
	Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Continued on Next Page

		Page: 5/6
Toxicity of the Products of Biodegradation	Not available.	
Special Remarks on the Products of Biodegradation	Not available.	

7.25

AND THE PROPERTY OF THE PROPER

Section 13. Disp	osal Considerations
Waste Information	Cured products may be landfilled. Uncured product must be handled according to local regulations.
Waste Stream	Consult your local authority. Consult your local hazardous waste management for advice.
Consult your local or reg	gional authorities.

DOT Classification	Combustible.		
	Label not required for shipments less than 450 liter or 119 gallons. Combustible Liquid, n.o.s. , 3, NA1993, I		
Marine Pollutant	Not available.		
Special Provisions for Transport	Quantity of 450 liters (119 gallons) or less are not regulated; the following apply to larger quantities: Combustible liquid,n.o.s., 3, NA1993, III. Quantity limitations: Passenger aircraft or railcar: 60 L. Cargo aircraft only: 220 L.		
ADR/RID Classification	Not controlled under ADR (Europe).		
IMO/IMDG Classification	Not controlled under IMDG.		
ICAO/IATA Classification	Not controlled under IATA.		

HCS Classification	Class: Combustible liquid having a flash point between 37.8°C (100°F) and 93.3°C (200°F).
U.S. Federal Regulations	All ingredients are in compliance with TSCA.
	SARA 302/304/311/312 extremely hazardous substances: No products were found.
	SARA 302/304 emergency planning and notification: No products were found.
	SARA 302/304/311/312 hazardous chemicals: No products were found. SARA 311/312 MSDS distribution - chemical inventory - hazard identification: No products were found.
	SARA 313 toxic chemical notification and release reporting: No products were found.
	Clean water act (CWA) 307: No products were found.
	Clean water act (CWA) 311: No products were found.
	Clean air act (CAA) 112 accidental release prevention: No products were found.
	Clean air act (CAA) 112 regulated flammable substances: No products were found.
	Clean air act (CAA) 112 regulated toxic substances: No products were found.
International Regulations	
EINECS	Not available.
DSCL (EEC)	This product is not classified according to the EU regulations.
International Lists	No products were found.
State Regulations	No products were found.
	California prop. 65: No products were found.

Section 16. Other Information

Label Requirements

Combustible liquid.

Rapid polymerization occurs upon contact with water or alkaline sustances. Skin inflamation or burns may


occur upon contact during this polymerization.

Will bond skin.

May cause mucous membrane and respiratory tract damage.

Use with adequate ventilation.

Hazardous Material **Information System** (U.S.A.)



National Fire Protection Association (U.S.A.)



References

-Manufacturer's Material Safety Data Sheet.

Other Special Considerations Skin, lips, eyelids or other body part bonded by cyanoacrylate are best separated by passive nonsurgical first aid.

Generaly warm water and gentle manipulation will break the cyanoacrylate bond.

Validated by Company on 12/3/2001.

Verified by Company.

Printed 12/3/2001.

Monday-Friday, 830-500pm, 513-779-7300 EST. OR 800-424-9300 - 24 hours

The data contained herein is based upon information that The Nail Superstore believes to be reliable. Users of this product have the responsibility to determine the suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and involved in said use. All statements or suggestions are made without warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material or results to be obtained form the use thereof.