Material Safety Data Sheet

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Artisan EZ Dipper Top Contact Information
Distributor: The Nail Superstore Tel: 847-260-4000

3804 Carnation St, Franklin Park, IL 60131 Emergency Telephone: 352-323-3500

2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components%ACGIHTLVOSHA PELOTHEREthyl Cyanoacrylate80-1000.2 ppm TWANoneNone7085-85-0

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

 Physical state: Liquid
 HEALTH:
 2

 Color:
 Clear Colorless
 FLAMMABILITY:
 2

 Odor:
 Sharp, Irritating
 PHYSICAL HAZARD:
 1

Personal Protection: See Section 8

WARNING: MAY CAUSE EYE AND RESPIRATORY IRRITATION.

BONDS SKIN IN SECONDS.

Potential Health Effects

Inhalation: Exposure to vapors above the established exposure limit results in respiratory irritation

which may lead to difficulty in breathing and tightness in the chest.

Skin contact: Bonds skin in seconds. May cause skin irritation. Allergic reactions are possible.

Cyanoacrylates generate heat on solidification. In rare circumstances a large drop will burn

the skin. Cured adhesive does not present a health hazard even if bonded to the skin.

Eye contact: Irritating to eyes. Causes excessive tearing. Eyelids may bond.

Ingestion: Not expected to be harmful by ingestion. Rapidly polymerizes (solidifies) and bonds in mouth.

It is almost impossible to swallow.

Existing conditions aggravated by

exposure: Skin , eye, and respiratory disorders.

GHS Classification Flammable liquids (Category 4)

Skin irritation (Category 2) Eye irritation (Category 2A)

Specific target organ toxicity – single exposure (Category 3)

GHS Label elements, including precautionary statements:

 $\langle \hat{\cdot} \rangle$

Warning

Pictogram: Signal word:

Hazard statement(s):

H227: Combustible liquid.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H335: May cause respiratory irritation.

Precautionary statement(s):

P261: Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P305+ P351+ P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses. If present and easy to

do. Continue rinsing.

FIRST AID MEASURES

Remove to fresh air. Prolonged or repeated elevated exposure may cause allergic reactions with asthma-

like symptoms in sensitive individuals.

Do not pull bonded skin apart. Wash with soap and water. Gently peel apart using a dull instrument. Skin contact:

If skin is burned due to the rapid generation of heat by a large drop, seek medical attention. If lips are bonded, apply warm water to the lips and encourage wetting and pressure from saliva in mouth. Peel

or roll lips apart. Do not pull lips apart with direct opposing force.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. Get medical attention. If eyelids are

> bonded closed, release eyelashes with warm water by covering with a wet pad. Do not force eye open. Cyanoacrylate will bond to eye protein and will cause a lachrymatory effect which will help to debond the adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. Medical attention should be sought in case solid particles of polymerized cyanoacrylate trapped behind the eyelid

caused abrasive damage.

Ingestion: Peel or roll skin apart. Adhesive becomes solid in contact with saliva and may adhere to inside of mouth.

Saliva will lift adhesive in 1-2 days. Avoid swallowing solid adhesive after detachment. Not a toxic product.

Notes to physician: Surgery is not necessary to separate accidentally bonded tissues. Experience has shown that bonded

tissues are best treated by passive, non-surgical first aid. If rapid curing has caused thermal burns they

should be treated symptomatically after adhesive is removed.

5. FIRE-FIGHTING MEASURES

Flash point: ≥80°C (176°F) Tagliabue closed cup

Flammable/Explosive limits-lower %: Not determined Flammable/Explosive limits-upper %: Not determined

Extinguishing media: Dry powder. Foam. Water spray. Carbon dioxide.

Special fire fighting procedures: Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

Unusual fire or explosion hazards: None

Hazardous combustion products: Trace amounts of toxic and/or irritating fumes may be released and the use of

breathing apparatus is recommended.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions: Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Clean-up methods:

Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mist. Keep container closed

when not in use

Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly Storage:

closed until ready for use. Recommended storage temperature:2-8 °C.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls: Use positive down-draft exhaust ventilation if general ventilation is insufficient to maintain vapor

concentration below established exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure limit(s). Observe OSHA

regulations for respiratory use (29 CFR 1910.134).

Use nitrile gloves and aprons as necessary to prevent contact. Do not use PVC, nylon or cotton. Skin protection:

Eye/face protection: Chemical splash goggles or safety glasses with side shields.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Clear Colorless Color: Sharp, Irritating Odor: **Odor Threshold:** 1-2 ppm

Vapor pressure: Less than 0.2 mm Hg at 25°C (77°F)

pH: Not applicable

Boiling point/range: Greater than 149°C (300°F)

Not determined Melting point/range: Specific gravity: 1.05 at 20°C Vapor density: Approximately 3 Evaporation rate: Not available

Solubility in water: Polymerizes in presence of water

Partition coefficient (n-octanol/water): Not determined

VOC content: Less than 2%; 20 g/L (California SCAQMD Method 316B) (estimated)

10. STABILITY AND REACTIVITY

Stability: Stable under recommended storage conditions

Hazardous polymerization: Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.

Hazardous decomposition products: Nor

Incompatability: Polymerized by water, alcohol, amines, alkaline materials and direct UV.

Conditions to avoid: Avoid temperature above 80°C (176°F), moisture and alkaline.

11. TOXICOLOGICAL INFORMATION

Product toxicity data: Acute oral LD50 >5000mg/kg (rat)(estimated).

Acute dermal LD50 >2000mg/kg (rabbit)(estimated).

Carcinogen Status

Hazardous components	NTP Carcinogen		OSHA
Ethyl Cyanoacrylate 7085-85-0	No	No	No

Literature Referenced Target Organ & Other Health Effects

Health Effects Hazardous	Health Effects/Target Organs
Ethyl Cyanoacrylate 7085-85-0	Allergen, Irritant, Respiratory

12. ECOLOGICAL INFORMATION

Ecological information: Not known

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of in accordance with Federal, State and local regulations.

EPA hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR):

Proper shipping name: Combustible liquids, n.o.s. (Cyanoacrylate ester)

Hazard class or division: Combustible liquid

 Identification number:
 None

 Packing group:
 None

 Exceptions:
 None

 Marine pollutant:
 None

International Air Transportation (ICAO/IATA):

Proper shipping name: Aviation regulated liquids, n.o.s (Cyanoacrylate ester)

 Hazard class or division:
 Unrestricted

 Identification number:
 None

 Packing group:
 None

 Exceptions:
 None

Water Transportation (IMO/IMDG):

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
Packing group:
Marine pollutant:
None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:

All ingredients in this mixture are in compliance with TSCA.

TSCA 12 (b) Export Notification: None. CERCLA/SARA Section 302 EHS: None.

CERCLA/SARA Section 311/312: Immediate Health Hazard, Delayed Health Hazard, Fire, Reactive

CERCLA/SARA 313: None

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information
CEPA DSL/NDSL Status:

WHMIS hazard class: European Community

EEC Label symbol and classification:

All components are listed on or are exempt from listing on the Domestic Substances List.

B.3, D.2.B



16. OTHER INFORMATION

DISCLAIMER:

The data contained herein is based upon information that The Nail Superstore believes to be reliable. Users of this product have the responsibility to determine the suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and involved in said use. All statements or suggestions are made without warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material or results to be obtained from the use thereof.